




Accord 90

Multi-purpose alkyd enamel

- ✓ Gloss
- ✓ High opacity and coating hardness
- ✓ Can be tinted



Description	
Properties	<p>Gloss alkyd enamel for interior and exterior use.</p> <ul style="list-style-type: none"> ✓ Created using "WA new technologies" ✓ Contains an opalescent polymer for better opacity. ✓ Spreads over the surface well, creating an ideally smooth semi-matt coating. ✓ High colour and gloss stability. ✓ Has weak odour due to the use of highly purified White-spirit. ✓ Forms a hard coating ✓ The surface is resistant to exposure to mild solvents (for example, White Spirit). <p>Maximum permissible EU VOC content for this product (subcat. d): 300g/L; maximum VOC content in the product <300g/L.</p> <p>Gloss:</p> <ul style="list-style-type: none"> • gloss (approximately 90) in accordance with ISO 2813
Purpose	For painting doors, window frames, furniture parts, radiators, fences, gratings and garages; both interior and exterior use.
Types of surfaces for painting	Wooden, metal as well as masonry plastered etc.
Quality standards and labels	<ul style="list-style-type: none"> ✓ Inside Special Opaque Polymers : the use of opalescent polymers in in alkyd paints; pigments are distributed evenly around the polymers, which improves coverage ✓ ISO 2813 [Paints and varnishes -- Determination of specular gloss of non-metallic paint films at 20 degrees, 60 degrees and 85 degrees] – techniques for measuring gloss and wear resistance parameters. ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE. ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and OHSAS 18001:2007.
Product specifications	

Surface preparation before painting	The surface to be painted must be degreased, cleaned from dirt and dry. Clean previously painted surfaces from peeling paint; sandpaper glossy surfaces until they are matt. Fill dents with putty. If necessary, pre-treat metal surfaces with anticorrosive primer first. Pre-treat wood chipboard, wood fibre board and other porous surfaces with suitable primer or paint diluted with white spirit (up to 10% of the paint volume).
Application	Stir the paint thoroughly before application. Apply 1-2 coats at the temperature between 10 °C and 25 °C and relative humidity not exceeding 80%. Time the painting process so that the treated surface can dry before the evening dew falls. Do not perform the application in direct sunlight, when the weather is too cold, in the rain or fog.
Care for the painted surface	The coating reaches its peak hardness and wash resistance in about 7 days; in the meantime, treat the surface with care. If cleaning is necessary, the surface can be lightly wiped with a soft sponge or cloth during this period. We recommend using water and neutral or medium alkaline detergents (pH below 9) for cleaning. Thoroughly wash the surface with clean water and dry it after cleaning.
Colour	White.
Tinting	Machine tinting according to the Eskarocolor system (bases A).
Consumption	8-10 m ² /L. на каждый слой
Thinner	White-Spirit
Drying time	The surface is not sticky in about 5 hours; ready for another coat to be applied in 24 hours at the temperature of +20 °C and the relative humidity of 50%.
Tools	Brush, Roller (pile length: 10-14 mm), airless spray gun (nozzle: 0.021–0.027").
Tool cleaning	Clean the tools with white spirit after completing work.
Additional information	
Frost resistance	None.
Min shelf life	3 years
Storage conditions	Store and transport in a tightly closed container at the temperature between +5°C and +30°C. Protect from exposure to freezing and direct sunlight.
Safety precautions	The product is not classified as dangerous according to CLP Regulation (EC) n° 1272/2008. Contains Butan-2-one oxime, Repeated exposure may cause skin dryness or cracking Cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	1,kg/L.
Volume/weight:	0,9 L – 2,25 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaro.ua/kontakty_ukr/</p>	