



Aura STARK

Alkyd enamel for floor

- ✓ Economical consumption
- ✓ Wearproof
- ✓ Long lasting shine



Description	
Properties	<p>Enamel alkyd PF-266</p> <ul style="list-style-type: none"> ✓ Glossy ✓ High covering ability. ✓ Easy application. ✓ Reliable protection of the painted surface from mechanical stress. ✓ Economical consumption. ✓ Fine decorative properties. ✓ Received hygienic conclusion of the Ministry of Health of Ukraine.
Purpose	PF-266 STARK alkyd enamel is intended for new and previously painted wooden floors and stairs used indoors.
Types of surfaces for drawing	New and previously painted wooden floors, stairs and other surfaces used indoors.
Quality standards	
Specifications	
Preparation surface	<p>Unpainted surface. Unevenness leveling putty on wood. To grind a surface with a fine-grained emery cloth. Clean from dust, dirt and grease.</p> <p>Previously painted surface. Remove peeling paint with a scraper or remover. Unevenness leveling putty on wood. To grind the puttied areas with fine-grained emery cloth. The surface must be dry and free from dust.</p>
Drawing	Before using the enamel must be thoroughly mixed. If necessary, dilute the enamel with white spirit, solvent (no more than 5% of the total enamel volume). To form a durable protective coating, it is recommended to apply the primer in 2 layers with intermediate drying between layers for at least 24 hours. Apply at a temperature of surface, enamel and air from + 5°C to + 35°C, relative humidity less than 80%. Apply the next layer after the previous one is completely dry.
Color	Ready colors according to the catalog.
Consumption	120-180 g / m ² per layer. The enamel consumption is influenced by the type of surface and its preparation.

Drying time	The drying time of 1 layer at a temperature of + 20°C and a relative humidity of 65% is not less than 24 hours. Temperature, relative air humidity and film thickness affect the drying rate.
Working tools	Brush or roller.
Cleaning tools	Immediately after use, rinse with white spirit and then with warm water and cleanser. Dried enamel is mechanically cleaned.
Composition	Suspension of pigments, fillers and functional additives in the solution of alkyd varnish and solvent.
Additional Information	
Frost resistance	Being
Warranty period of storage	Warranty period of storage is 24 months from the date printed on the package.
Storage conditions	Store and transport in an original tightly closed container. Keep away from moisture, heating appliances and direct fire, as well as direct sunlight.
Precautionary measures	Keep out of the reach of children. Avoid contact with eyes and skin. When carrying out painting works, as well as after their completion, it is necessary to ventilate the room thoroughly. Rubber gloves should be used to protect hands, and a respirator should be used to protect respiratory organs. Keep away from fire!
Recycling	Do not pour into drains, reservoir or on the ground. Dispose of product residues and containers at organized waste collection sites.
Weight	0,9 kg - 2,8 kg
<p>The above, up-to-date information in the Technical Description is based on our practical experience, as well as on our laboratory testing of products and is provided in all the volume available to us. The presented information can be used as recommendations when choosing products and working methods for its application. The manufacturer guarantees the conformity of products with the specified technical specifications only in case of compliance with the rules of transportation, storage, preparation, preparation, use, operation, which are given in this Technical Description. The manufacturer does not have the ability to foresee and control all conditions for the use of products, as well as various factors that affect its use and further operation. Taking into account the variety of materials of surfaces and specific conditions of objects on which products are used, the Consumer should carefully check the products for their suitability for a particular object, taking into account all possible conditions of its use not specified in this Technical Description. The presented information does not relieve the Consumer from responsibility for the quality of work. In case of non-compliance by the Consumer with the requirements of the Technical Description (Operating Instructions), the use of products for other purposes, the Manufacturer shall not be legally responsible for any damage caused to the Consumer. The manufacturer, on the basis of new product knowledge, reserves the right to amend the Technical Description in the prescribed manner. The text of the new edition of the Technical Description is placed by the Manufacturer on the website www.eskaro.ua with the date of introduction and the number of the new edition of the Technical Description. When a new edition of this Technical Description is released, the previous edition loses its force and is removed by the Manufacturer from the site. Additional information can be obtained from the representative of the Manufacturer or on the website www.eskaro.ua</p>	
Revision of Technical Description №01 as of March 15th, 2019.	