

Objekt

Insulating deep matt acrylate paint



- ✓ Reinforced with synthetic resin
- ✓ Effectively isolates contaminants
- ✓ Excellent adhesion to various substrates



Description	
Properties	<p>Acrylate water-based paint for repainting difficult dirt in rooms with high operational load.</p> <ul style="list-style-type: none"> • Well isolates stains from nicotine, soot, soot and rust, traces of water leaks, etc. • Quickly and effectively repaints heavily soiled surfaces, forming an absolutely matte dense coating. • Serves as a reliable barrier against yellowness. • Good hiding power. • Increased adhesion to various substrates, including surfaces painted with alkyd and oil paints. • Reinforced with synthetic resin. • Particularly suitable for emergency repairs on large sites. <p>The content of VOC in the product corresponds to the maximum allowable for subgroup i - 140 g/l. The maximum VOC content in the product is <140 g/l.</p> <p>Shine:</p> <ul style="list-style-type: none"> • deep matt (approx. 2) according to EN 13 300. • deep matt (approx. 2) according to ISO 2813. <p>Wear resistance:</p> <ul style="list-style-type: none"> • Class 3 according to EN 13 300 (ISO 11998). Load class: RL 04 Extreme loads and high demands in dry rooms according to RYL 2012.

Purpose	Designed for repainting heavily soiled surfaces in rooms with high operational load, such as entrances, stairwells, corridors, hotels, ceilings in kitchens. Suitable for use as a primer for waterborne paints.
Types of surfaces to be painted	New or previously painted surfaces made of concrete, aerated concrete, gypsum boards, on brick, putted, plastered surfaces with water-based, alkyd or oil paints. For interior work.
Standards and quality marks	<ul style="list-style-type: none"> ✓ EN 13 300 - standards for classifying the parameters of hiding power, gloss level, resistance to wet abrasion for water-borne paints and varnishes for interior walls and ceilings. ✓ ISO 11 998, ISO 2813 – methods for measuring gloss and wear resistance parameters. ✓ VOC (Volatile Organic Compounds) content according to European Union Directive 2004/42/CE ✓ The quality of products and services is guaranteed by the environmental, health and safety management system in accordance with ISO 9001: 2015; ISO 14001:2015 and OHSAS 18001:2007.
Specifications	
Surface preparation before painting	The surface to be painted must be free from loose and flaking material, dirt and dust. Fill cracks and crevices with a suitable filler (Fine Filler, Aqua Filler, etc.). Before you start painting, we recommend washing the surface with a 3-5% soda solution or a detergent containing ammonia solution, rinse with water and dry. Surfaces that are frequently wet and susceptible to mold should be treated with Biotol or Biotol Spray before painting. Newly putted surfaces should be primed with Aquastop or Tiefgrund.
Application	Stir the paint thoroughly before use. It is desirable to mix tinted paint in one container.
Color	White (base A).
Tinting	Eskarocolor tinting system (base A).
Cost per layer	6-10 m ² /l.
Thinner/solvent	Water.
Drying time	For the second layer - 1 ... 1.5 hours, complete drying - 2 hours at 20°C and 50% relative humidity.
Tools	Roller, brush.
Cleaning tools	Upon completion of work, wash with soap and water.
Compound	Acrylic copolymer, modified alkyd resin, titanium dioxide, fillers, functional additives, corrosion inhibitor, water. Maximum allowable VOC content for the product (subgroup i): < 140g/l (g/l). This product contains max < 140 g/L (g/l) in VOC.
Information	
Frost resistance	Not frost-resistant during storage.
Warranty period of storage	3 years.
Storage conditions	Store and transport in a tightly closed package at temperatures from +5°C to +30 °C. Keep away from cold and direct sunlight.
Precautionary measures	According to the Regulation on the classification, labeling and packaging of chemicals and mixtures No. 1272/2008 (CLP Regulation), these products are not classified as hazardous. Follow the general rules of occupational health. Keep out of the reach of children. If medical advice is needed, have product container or label at hand. To prevent accidents, it is recommended to use basic personal protective equipment with the CE mark. Use water to clean paint-contaminated surfaces and objects.
Disposal	Do not pour into sewer. Avoid release to the environment. Dispose of packaging, dry general waste and liquid waste in accordance with local regulations.
Density	1,4 kg/L.
Volume	0,9 l – 2,7 l – 9 l
The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaro.ee/kontaktid/main_office_contacts/	
Technical description revision №01 from 21.07.2022.	